



Fire Extinguisher

Dry Chemical Extinguisher



- ABC (Monoammonium Phosphate) Dry Chemical, Extinguishing Agent by Furex Germany.
- Approve by TIS.

DRY CHEMICAL EXTINGUISHER MULTIPURPOSE

SPECIFICATION	SIZE			
	4.5 Kg.	6.8 Kg.	7 Kg.	9 Kg.
Weight of Container	2.6 Kg.	3.4 Kg.	3.4 Kg.	4.4 Kg.
Weight of Agent	4.5 Kg.	6.8 Kg.	7.0 Kg.	9.0 Kg.
Gross weight	7.1 Kg.	10.2 Kg.	10.4 Kg.	13.4 Kg.
Over all high	500 mm.	560 mm.	560 mm.	590 mm.
Shell diameter	138 mm.	152 mm.	152 mm.	176 mm.
Working pressure	195 psi. 1.34 MPa.	195 psi. 1.34 MPa.	195 psi. 1.34 MPa.	195 psi. 1.34 MPa.
Discharging time	15 Sec.	20 Sec.	20 Sec.	25 Sec.
Shooting Range	6~8 M	6~8 M	6~8 M	6~8 M



FIRE FIGHTING EQUIPMENT



Fire Extinguisher

Carbon Dioxide (CO2) Fire Extinguisher



- Hand-held units use aluminum cylinders with a baked-on polyester enamel coating to withstand harsh environments. All units manufactured to USCG, ANSI/UL 154 and ANSI/UL711 Standards and use DOT compliant cylinders.

TYPICAL USES: Refineries, shipboard, laboratories, construction sites, chemical plants, and manufacturing facilities.

Model	5CD	10CD	15CD	20CD
Part Number	45100	45600	46100	46600
Agent Capacity	5 lbs. (2.27 kg.)	10 lbs. (4.54 kg.)	15 lbs. (6.80 kg.)	20 lbs. (9.07 kg.)
UL Rating	5 B:C	10 B:C		
Discharge Time	8 seconds	10 seconds	15 seconds	20 seconds
Range	4-8 ft. (1.2-2.4 m.)			
Bracket	Wall			
USCG Approval	Type B:C Size I		Type B:C Size II	
Ship Wt.	13.75 lbs. (6.3 kg.)	27.75 lbs. (12.6 kg.)	37.75 lbs. (17.1 kg.)	49.0 lbs. (22.2 kg.)
Height	17.375 in. (44.1 cm.)	19.75 in. (50.2 cm.)	26.375 in. (67 cm.)	26.875 in. (68.2 cm.)
Width	8.25 in. (21 cm.)	12 in. (30.5 cm.)		13 in. (33 cm.)
Diameter	5.25 in. (13.3 cm.)	6.89 in. (17.5 cm.)		8 in. (20.3 cm.)