



FIRE FIGHTING EQUIPMENT



**Nozzle**

**1.5" Selectable Gallonage Model 366**



- Strong Lightweight Aluminum Alloy Construction.
- With Pistol Grip.
- 30-60-95-125 GPM (115-230-360-475 LPM).
- 1.5" Inlet.
- Ideal For Use With Eductors And Foam Tube.
- Service Kit 1001.
- FM Approved.



**Nozzle**

**Mid-Range Selectable Gallonage Model 367**



- Strong lightweight aluminum alloy construction.
- With Pistol Grip.
- 95-125-150-200 GPM (360-475-550-750 LPM).
- 1.5" Inlet.
- Service Kit 1002.



**Nozzle**

**Nozzle Model SG-7515**



- Nozzle: Flow Setting 265 - 380 - 500 - 600 LPM., 1-1/2" BSP Swivel., Weight: 1.940 g., Length: 22.5 cm.
- TIP: 1-1/2" BSP Swivel., Weight: 1.255 g., Length: 15.5 cm.



**Nozzle**

**Nozzle Model SG-3012**



- Nozzle: Flow Setting 115 - 230 - 360 - 475 LPM., 1-1/2" BSP Swivel., Weight: 1.940 g., Length: 22.5 cm.
- TIP: 1-1/2" BSP Swivel., Weight: 1.255 g., Length: 15.5 cm.