




Nozzle

Leader Line Dual Ball Valve Model A99



a	b
2-1/2"	1-1/2"
2-1/2" x 1-11/2"	
A	4-13/32"
B	5-35/64"
C	6-7/64"
D	8-15/64"

- Chrome plated furnished with rocker lug swivels.
- Red painted.



Portable Monitor

Single Inlet Portable Monitor Model 622-1,622-2



Model 622-1



Model 622-2

- Durable, lightweight alloy construction.
- Dual application use as portable monitor or add the top mount flange for deck mount use.
- Sturdy extended ground base help maintain stability.
- Compact folding base can be stored in any truck compartment or pre-connected in the hose bed.
- Vertical travel from 90 degree above to 50 degree below horizontal with safety stop at 30 degree above horizontal.
- Full, unobstructed 3" waterway for low friction loss.
- Fully enclosed worm gear to protect from foreign elements.
- "Built-in" pressure gauge.
- For water or foam application.

**High Volume :**

1000 GPM in portable mode with single inlet (Style 622-1)

800 GPM in portable with double 2-1/2" inlet (Style 622-2)



Style	Flow	Thread		Dimensions			Weight
		Inlet	Outlet	Width	Depth	Height	
622-1	1,000 GPM	4" or 5"	2.5"	25"	26"	16"	28 lbs.
622-2	800 GPM	(2) 2.5"	2.5"	25"	26"	16"	27 lbs.

FIRE FIGHTING EQUIPMENT

