



# 2008 Series Retractor

## Specification and Data Sheet

	<u>Unit</u>	<u>Weight</u>	<u>Length</u>	<u>Harness Attachment</u>	<u>Anchor Attachment</u>
<b><u>Part Numbers</u></b>	2008-P07	3.5 lb.	7 ft.	3/4" d/l snaphook	N/A
	2008-PH07	4.3 lb.	7 ft.	3/4" d/l snaphook	Carabiner
	2008-PH07L	3.3 lb.	7 ft.	Web Loop	Carabiner
	2008-P09	4.1 lb.	9 ft.	3/4" d/l snaphook	N/A
	2008-PC09	6.0 lb.	9 ft.	3/4" d/l snaphook	Large Carabiner
	2008-PC09AL	5.2 lb.	9 ft.	3/4" Aluminum carabiner	Large Aluminum Carabiner
	2008-PH09	4.9 lb.	9 ft.	3/4" d/l snaphook	Carabiner
	2008-PS09	4.1 lb.	9 ft.	5/8" d/l carabiner	N/A
	2008-PH10L	4.2 lb.	10 ft.	Web Loop	Carabiner
	2008-P119125	5.6 lb.	11 ft.	3/4" d/l snaphook	3/4" d/l snaphook
	2008-PC11	6.6 lb.	11 ft.	3/4" d/l snaphook	Large Carabiner
	2008-PH11	5.6 lb.	11 ft.	3/4" d/l snaphook	Carabiner
	2008-PH11C	5.5 lb.	11 ft.	5/8" d/l carabiner	Carabiner

**Description** Polyester webbing self-retracting lanyard.

**Designed Working Load** 310 lb., including tools.

**Standards Compliance** ANSI A10.14-1991, Z359.1-1992 (R1999), A10.32-2004; OSHA 1910.66, 1926.500

**Dimensions** Housing: 4.5" x 4.0" x 3.0"

**Material** Neoprene covered steel housing. Polyester webbing. Steel Hardware.

**Additional Notes** SM/RTC Retractor® includes a Safe-T-Fold® stress indicator for easy visual indication of a fall arrest. Every 2008 also includes a stainless steel top swivel.

