

sellstrom.

Emergency Shower

SentryWash® Eye Wash & Shower Safety Station



- Shower Head: 10" blue ABS plastic shower head delivers 30 gPM at 30 PSI. Spray pattern is 20" diameter at 60" above floor.
- Shower Valve: 1" IPS chrome plated brass stay-open ball valve, furnished with stainless steel actuating arm and stainless steel pull rod. Valve is made in the USA.
- Eye Wash Outlet Head Assembly: Two outlet heads. Each head has self-regulating flow control (to assure soft, balanced flow), filter to remove debris from water, and float-off dust cover. All wearing components are located in head for ease of service. Heads are mounted on chrome plated brass supply arms.
- Eye Wash Bowl: 11 1/2" stainless steel.
- Eye Wash Valve: 1/2" IPS chrome plated brass stay-open ball valve. Activated by epoxy coated cast aluminum flag handle.
 Valve made in USA.
- Pipe and Fitting: 1 1/4" IPS Schedule 40 hot-dipped galvanized steel pipe and fittings with 9" cast aluminum floor flange.
- Supply: 1g" IPS female top or side inlet.
- Waste: 1 1/4" IPS female outlet.
- Quality Assurance: Eye wash frame is factory assembled and individually water tested prior to shipment.
- Meets ANSI Z358.1-2004 Standards.

Eye Wash / Drench Shower - Cycloac Shower Head with 2 Heads, Cycolac Shower Head, Corrosion Resist. - All Stainless Steel Construction (31 lbs.) Model 90560.

